



Vida Select Graded Batten



Product Data and Packaging

Batten Size	Lngths/Bundle	Bundles/pack	Pcs/pack
25x50	10	44	440
25x38	10	56	560
19x38	10	70	700

Lengths available/mts: **3.6, 3.9, 4.2, 4.5, 4.8, 5.1, 5.4**

Batten tolerance:

Thickness - 0mm + 3mm. Width - 3mm + 3mm

Quality Assurance

Roofers Choice Graded Batten meets all aspects of BS5534:2003 + A1:2010 with the exception of a final grade for knots and wane.

This British Standard assesses:

Dimensions/full measure	Species
Length	Fissures
Slope of grain	Rate of growth
Distortion	Decay & Insect attack
Identification & marking	

Roofers Choice Graded Batten is kiln dried to ensure that it reaches an average of below 20% moisture content and is treated to BS8417: 2003 that gives an expected life of 60 years with regard to insect attack and wood rotting fungi (when used correctly). This preservative is Celcure AC800 and is applied in a high pressure process.

Roofers Choice Graded Batten is a high quality roof batten that meets all aspects of BS5534 : 2003 + A1 :2010 with the exception of a final grade for knots and wane, which must be carried out on site.

Produced by Vida Wood SE, Swedens largest independent producer of timber products. **Roofers Choice Graded Batten** is only produced from Swedish Redwood (PNSY) or Swedish Whitewood (WPCA) at eight strategically placed saw mills. These saw mills are accredited by S.P in Sweden (Svenska Proving), which is the Swedish equivalent of our British Standards.

Storage

Roofers Choice Graded Batten can be stored outside but the colour will fade over time. This will not effect the lifespan of the product.



Head Office: 114 Eckington Road,
Coal Aston, Dronfield S18 3AY

Telephone: 01246 292816 Fax: 01246 292867
Telephone: 01246 268084 FAX: 01246 268094

Website: www.mercurybuildingproducts.com
email: danny@vaprfree.co.uk